



AMERICAN LIGHTING
 11775 East 45th Avenue
 Denver, CO 80239
 Phone (303) 695-3019
 Fax: (303) 695-7633

Quote #: 2365189
 Ship Via: None
 Customer ID:
 PO Number: SEAS - Cristal - LS-MS-24

AMERICAN LIGHTING QUOTE

Bill To:	Ship To:
----------	----------

City of Fort Bragg
 Cristal Munoz
 416 N. Franklin Street

 Fort Bragg, CA 95437
 USA,

City of Fort Bragg
 Munoz, Cristal
 416 N. Franklin Street

 Fort Bragg, CA 95437
 USA

	<u>Price</u>	<u>Discount %</u>	<u>Adj Price</u>	<u>Qty</u>	<u>Unit</u>	<u>Extended Price</u>
1 LS-MS-24-BK: 330' LT STRG,MED BASE,2' SCKT SP,SUSPENDED SCKT,BL	\$520.65	0.00	\$520.65	2.00	Each	\$1,041.30
2 PS14-E26-WW: PREM LED S14 LAMP,TRANSPARENT GLASS,1.4W,120V,E26,	\$157.40	0.00	\$157.40	14.00	BX25	\$2,203.60
3 LS-CABLE-500: 500' SPOOL OF 1/8" CABLE FOR BULK CGLS INSTALL	\$146.80	0.00	\$146.80	2.00	Each	\$293.60
4 LS-LOCK-4: BAG OF 4 1/8" CABLE LOCKS, USE WITH LS-CABLE-500,CGL	\$31.65	0.00	\$31.65	2.00	Each	\$63.30
5 LS-TT: TENSIONING TOOL FOR CGLS INSTALLATION CABLE	\$108.90	0.00	\$108.90	1.00	Each	\$108.90
6 LS-M/MS-END: BLACK, END CAP FOR MED BASE LIGHT STRING,3/8" DIA,	\$0.75	0.00	\$0.75	1.00	Each	\$0.75
Merchandise Total:						\$3,711.45

In order to avoid delays and to validate quoted price, please either submit a copy of this quote with your purchase order or reference this Quote # (located at the top right hand corner of the Quote) on your purchase order.

Pricing on this quote is valid until: Tuesday, October 4, 2022

Products and Pricing on this quote are subject to American Lighting's Terms & Conditions.

All the parts listed and their corresponding quantities are based on how we understood your request. Some accessories and their quoted quantities were estimated and may not be the actual needed quantities. American Lighting cannot be held responsible for any misunderstanding of what is needed or how it will be used for your project.

Created By: Troy Romero on 8/5/22 12:22 pm



Features

- Available in E26, E17, and E12 base options
- Formulated PVC sockets form a tight seal around bulbs to preclude the entrance of water and moisture
- Suspended socket has T-mold with mounting hole; Non-suspended socket has two mounting ears built into the base
- Use Commercial Grade Light String with Long Life Pro Decorative lamps (sold separately)

Available Colors



Black

Listing / Ratings



LS2 Only

Commercial Grade Light String

Use Commercial Grade Light String in reels, interconnect-able kits, or cord and plug sets with three socket size and spacing combinations for decorative/event/festive lighting applications. Suitable for outdoor, year-round use. For spans up to 20 feet, use eye bolts and plastic ties to anchor ends. For spans longer than 20 feet, use catenary cable (sold separately) with plastic ties at each socket.

Technical Information

Series	LS / LS2*
Input Voltage	120V AC, 60Hz
Wattage	Max per socket: 25W (E26) / 10W (E17 / E12)
Max Run	See individual product
Socket	E26 (medium)
Spacing	24" (E26) / 15" (E17) / 12" (E12)
Cuttable	Yes**
IP Rating	IP64**
Rating	Indoor/Outdoor; Suitable for year-round use*
Rated Life	Varies by lamp used

* All LS products are non-rated; LS2 interconnect-able kits are cTUVus Listed to UL standard UL588 for wet location all-year use, however safety rating is void if product is cut. Not intended for installation in ceilings, soffits, cabinets or other enclosed spaces.

**For non-cut cTUVus Listed LS2 product, interconnected strings must be properly sealed and strain relief protected with electrical tape at each connection point. For non-rated LS product, any cut ends must be sealed with LS-M/MS-END and/or electrical tape (ensure proper seal to preclude entrance of water).

Light String Accessories

LS-M/MS-END	Plastic End Cap (LS2 /LS)
M-PLUG-BK-SPT2-B	SPT-2 Slide On Male Plug (E17 / E12) - Qty 25



SPEKTRUM+

TRULUX LIGHTING SYSTEMS

TASK LIGHTING

DOWNLIGHTING

LINEAR LIGHTING
COMMERCIAL GRADE
LIGHT STRING

ARCHITECTURAL LIGHTING

POWER SUPPLIES

MEDIUM BASE (E26) cTUVus LISTED ORDERING INFORMATION 1200W Max (48ft)

ITEM NUMBER	LENGTH	SOCKETS	SOCKET SPACING	SOCKET TYPE	MAX WATTAGE	IP RATING	Rating
LS2-M-24-48-BK	48 ft	24	24 in	Non-suspended	25W per socket	IP64	TUV
LS2-MS-24-48-BK	48 ft	24	24 in	Suspended	25W per socket	IP64	TUV

* LS2 interconnectable kits are cTUVus Listed for wet location use; safety rating is void if product is cut. LS2 kits include 120V male plug + female socket.

MEDIUM BASE (E26) ORDERING INFORMATION 600W Max (48ft) / 1250W Max (100ft) / 1800W Max (330ft)

ITEM NUMBER	LENGTH	SOCKETS	SOCKET SPACING	SOCKET TYPE	MAX WATTAGE	IP RATING	Rating
LS-M-24-100-BK	100 ft	50	24"	Non-suspended	25W per socket	IP64	N/A
LS-M-24-BK	330 ft	165	24"	Non-suspended	25W per socket	IP64	N/A
LS-MS-24-100-BK	100 ft	50	24"	Suspended	25W per socket	IP64	N/A
LS-MS-24-BK	330 ft	165	24"	Suspended	25W per socket	IP64	N/A

* All LS products are non-rated. 100ft lengths include 120V plug + terminated end. 330ft Bulk reels include bare wire lead + bare wire tail.



INTERMEDIATE BASE (E17) BULK REELS ORDERING INFORMATION 1200W Max (330ft)

ITEM NUMBER	LENGTH	SOCKETS	SOCKET SPACING	SOCKET TYPE	MAX WATTAGE	IP RATING	Rating
LS-I-15-BK	330 ft	264	15"	Non-suspended	10W per socket	IP64	N/A

* All LS products are non-rated. 330ft Bulk reels include bare wire lead + bare wire tail.



CANDELABRA BASE (E12) BULK REELS ORDERING INFORMATION 1200W Max (330ft)

ITEM NUMBER	LENGTH	SOCKETS	SOCKET SPACING	SOCKET TYPE	MAX WATTAGE	IP RATING	Rating
LS-C-12-BK	330 ft	330	12"	Non-suspended	10W per socket	IP64	N/A

* All LS products are non-rated. 330ft Bulk reels include bare wire lead + bare wire tail.



SPEKTRUM+

TRULUX LIGHTING SYSTEMS

TASK LIGHTING

DOWNLIGHTING

LINEAR LIGHTING
PRO DEC S14 LAMP

ARCHITECTURAL LIGHTING

POWER SUPPLIES

Features

- SMD LED powered by on-board driver for 120V AC use in medium base (E26) sockets
- Nickel base resists corrosion
- Ultra clear glass lenses
- Dimmable with most CL or TRIAC dimmers*
- IP65 rated for wet location use
- cULus Listed for indoor and outdoor use
- Sold in boxes of 25 and cases of 200

Available CCT



2400K 2700K

Dimming Options

- CL (10-100%*)
- TRIAC (10-100%*)

Listing / Ratings



Pro Dec S14

A variety of LED S14 lamps for direct replacement of 11W incandescent versions saves 87% in running costs. The classic decorative bulb shape features a nickel base which resists corrosion and offers up to 60 lumens of long lasting, energy efficient LED light.

Technical Information

Series	PS14
Base	E26
Input Voltage	120V AC, 60Hz
CCT	2400K / 2700K
Wattage	1.4W
Lumens	Up to 60Lm (see individual product)
IP Rating	IP65
Dimmable	10-100%*
Rating	cULus Listed for indoor/outdoor use
Rated Life	25,000 hrs

*Minimum loads will apply

Ordering Information

PS14-E26-UWW	Transparent / Ultra Warm White (2400K) / 30Lm
PS14-E26-WW	Transparent / Warm White (2700K) / 36Lm
PS14-E26-WH	Transparent / Bright White (5500K) / 48Lm