



TABLE 5003.1.1(1)

MAXIMUM ALLOWABLE QUANTITY PER CONTROL AREA OF HAZARDOUS MATERIALS POSING A PHYSICAL HAZARD^{3, j, m, n, p} See Note q (200) NA NA 13,200^f 3,300[£] NA NA 45^d NA 10^{d} 0.25^g (0.25)g 0.25g (0.25)g $(0.25)^{g}$ (1)^g NA (50)g NA NA NA NA 0.25^g $(0.25)^{g}$ NA NA NA NA (150)^{d, e} NA 10d NA NA 120^{d} 30d $120^{d,h}$ NA $30^{d,h}$ NA NA NA 25^d

TABLE 5003.1.1(1)—continued

MAXIMUM ALLOWABLE QUANTITY PER CONTROL AREA OF HAZARDOUS MATERIALS POSING A PHYSICAL HAZARD^{a,j, m, n, p}

MATERIAL	CLASS	GROUP WHEN THE MAXIMUM ALLOWABLE QUANTITY IS EXCEEDED	STORAGE			USE-CLOSED SYSTEMS ^b			USE-OPEN SYSTEMS ^b	
			Solid pounds (cubic feet)	Liquid gallons (pounds)	Gas (cubic feet at NTP)	Solid pounds (cubic feet)	Liquid gallons (pounds)	Gas (cubic feet at NTP)	Solid pounds (cubic feet)	Liquid gallons (pounds)
Inert gas	Gaseous	NA	NA	NA	NL	NA	NA	NL	NA	NA
	Liquefied	NA	NA	NA	NL	NA	NA	NL	NA	NA
Organic peroxide	UD	H-1	1c, g	(1) ^{c, g}	NA	0.25 ^g	(0.25) ^g	NA NA	0.25 ^g	(0.25)g
	I	H-2	5 ^{d, e}	(5) ^{d, e}		1ª	(1) ^d		1 ^d	(1) ^d
	П	H-3	50 ^{d, e}	(50) ^{d, e}		50 ^d	(50) ^d		10 ^d	(10) ^d
	Ш	H-3	125 ^{d, e}	(125) ^{d, e}		125 ^d	(125) ^d		25 ^d	(25) ^d
	IV	NA	NL	NL		NL	NL		NL	NL
	V	NA	NL	NL		NL	NL		NL	NL
Oxidizer	4	H-1	1 ^g	(1) ^{c, g}	NA NA	0.25 ^g	(0.25)g	NA	0.25 ^g	(0.25)g
	3 ^k	H-2 or H-3	10 ^{d, e}	(10) ^{d, e}		2 ^d	(2) ^d		2 ^d	(2) ^d
	2	H-3	250 ^{d, e}	(250) ^{d, e}		250 ^d	(250) ^d		50 ^d	(50) ^d
	1	NA	4,000 ^{c, f}	(4,000)°, f		4,000 ^f	(4,000) [£]		1,000 ^f	(1,000) ^f
Oxidizing gas	Gaseous	H-3	NA	NA	1,500 ^{d,e}	NÄ	NA	1,500 ^{d,c}	NA	NA
	Liquefied	H-3	NA NA	(150) ^{d,e} NA	(150) ^{d,c}	NA	INA.	INA.		
Pyrophoric	NA	H-2	4c, g	(4)°, g	50°, g	18	(1) ^g	10°, g	0	0
Unstable (reactive)	4	H-1	1 ^{c, g}	(1)°, g	10 ^{e, g}	0.25 ^g	(0.25)g	2 ^{e, g}	0.25g	(0.25)g
	3	H-1 or H-2	5 ^{d, e}	(5) ^{d, e}	50 ^{d, c}	1 ^d	(1) ^d	10 ^{d, c}	1 ^d	(1) ^d
	2	H-3	50 ^{d, e}	(50) ^{d, o}	750 ^{d, e}	50 ^d	(50) ^d	750 ^{d, e}	10 ^d	(10) ^d
	l	NA	NL	NL	NL	NL	NL	NL	NL	NL
Water reactive	3	H-2	5 ^{d, e}	(5) ^{d, e}	NA NA	5 ^d	(5) ^d	NA	1 ^d	(1) ^d
	2	H-3	- 50 ^{d, e}	(50) ^{d, c}		50 ^d	(50) ^d		10 ^d	(10) ^d
	1	NA	NL	NL	[NL	NL		NL	NL

wholesale sales occupancies, the quantities of medicines, foodstuff or consumer products and cosmetics containing not more than 50 percent by volume of water-miscible liquids with the remainder of the solutions not being flammable shall not be limited, provided that such materials are packaged in individual containers not exceeding 1.3 gallons.

e. Maximum allowable quantities shall be increased 100 percent where stored in approved storage cabinets, day boxes, gas cabinets, gas rooms, exhausted enclosures or in listed safety cans in accordance with

1. Net weight of pyrotechnic composition of the fireworks. Where the net weight of the pyrotechnic composition of the fireworks is not known, 25 percent of the gross weight of the fireworks including

q. Where manufactured, generated or used in such a manner that the concentration and conditions create a fire or explosion hazard based on information prepared in accordance with Section 104.8.2.



THESE PLANS ARE ORIGINALLY PRINTED ON 22"x34" PAPER.

- 1 INCH --

Date MAY 1 '24

Scale AS NOTED

DCL

GKK

CFB2301

REVISIONS

PLAN REVIEW

NOT FOR

ENGINEERING

EER FIRE DEPARTMEN

BRAGG EW FIRE

CONSTRUCTION